

[POWER COMMANDER V]

2009 Yamaha FZ6R

Installation Instructions



PARTS LIST

- 1 Power Commander
- 1 USB Cable
- 1 CD-ROM
- 1 Installation Guide
- 2 Power Commander Decals
- 2 Dynojet Decals
- 2 Velcro
- 1 Alcohol swab

THE IGNITION MUST BE TURNED OFF BEFORE INSTALLATION!


YOU CAN ALSO DOWNLOAD THE POWER COMMANDER SOFTWARE AND LATEST MAPS FROM OUR WEB SITE AT:
www.powercommander.com

PLEASE READ ALL DIRECTIONS BEFORE STARTING INSTALLATION

Dynojet

2191 Mendenhall Drive North Las Vegas, NV 89081 (800) 992-4993 www.powercommander.com

POWER COMMANDER V INPUT ACCESSORY GUIDE




Optional Accessories such as Color LCD unit or Auto tune kit.

Wire connections:

To input wires into the PCV first remove the rubber plug on the backside of the unit and loosen the screw for the corresponding input. Using a 22-24 gauge wire strip about 10mm from its end. Push the wire into the hole of the PCV until it stops and then tighten the screw. Make sure to reinstall the rubber plug.

NOTE: If you tin the wires with solder it will make inserting them easier.



ACCESSORY INPUTS

Map -

The PCV has the ability to hold 2 different base maps. You can switch on the fly between these two base maps when you hook up a switch to the MAP inputs. You can use any open/close type switch. The polarity of the wires is not important. When using the Autotune kit one position will hold a base map and the other position will let you activate the learning mode. When the switch is "CLOSED" Autotune will be activated.

Shifter-

These inputs are for use with the Dynojet quickshifter. Insert the wires from the Dynojet quickshifter into the SHIFTER inputs. The polarity of the wires is not important.

Speed-




If your application has a speed sensor then you can tap into the signal side of the sensor and run a wire into this input. This will allow you to calculate gear position in the Control Center Software. Once gear position is setup you can alter your map based on gear position and setup gear dependent kill times when using a quickshifter.

Analog-

This input is for a 0-5v signal such as engine temp, boost, etc. Once this input is established you can alter your fuel curve based on this input in the control center software.

Crank-

Do **NOT** connect anything to this port unless instructed to do so by Dynojet. It is used to transfer crank trigger data from one module to another.




- 1 Remove the seat.
- 2 Prop the front of fuel tank up.
(Figure A shown with fuel tank removed which is not necessary)
- 3 Secure the PCV underneath the inner fairing panel using the supplied velcro (Fig. A). Make sure to use the alcohol swab to clean both surfaces before attaching.
- 4 Route the PCV harness down the left side of the air box and go towards the throttle bodies (Fig. B).
- 5 Unplug the wiring harness from the throttle bodies (Fig. C).
One connector is a WHITE 4 pin and the other is a CLEAR 6 pin.

FIG.D



6 Plug the connectors from the PCV into the harness (Fig. D).

FIG.E



7 Attach the ground wire of the PCV to the negative side of the battery (Fig. E).

8 Bolt the fuel tank back into place and reinstall the seat.

Speed input - PINK wire of 3 pin WHITE connector under fuel tank. Speed sensor is located on the engine case near the front sprocket cover.

Temperature input - Green/White wire of 6 pin clear connector under fuel tank (Same as PCV connection).

12v source for Auto tune - BLUE wire of tail light connector.